

Product Datasheet

T325A267 24 Port 1U UTP Unloaded Patch Panel

Rev. Date : 15.09.2022

Rev. Nr. : 000

Page Nr. : 1/1

OVERVIEW

Zemecs T325A267 is an unloaded patch panel which can be used with all Zemecs Category 5e-6- 6_A UTP keystone jacks inside 19" rack cabinets. When the label field is pushed from down, the cover opens 45 degrees enabling easy removal of labels.

The foldable cable organizer comes with a novelty cable tie free design. The product can also be used to terminate couplers and connectors used in other ELV systems.



FEATURES

- 24 Port 1U height
- Compatible with all Zemecs keystone jacks (Category 5e-6-6_A UTP)
- · Anti corrosion metal housing
- · With transparent label windows
- · With cable tie free foldable organizer

MATERIAL AND PHYSICAL SPECIFICATIONS

Housing Material	Electrostatic Powder Coated SPCC	
Front Panel Material	Flame Retardant Plastics, UL 94 V-0	
Cable Organizer	Electrostatic Powder Coated SPCC + Flame Retardant Plastics, UL 94 V-0	
Colour	Black	
# / Type Of Compatible Jacks	24 / UTP	
Labelling Field	Transparent Label Windows	
Supported Cable O.D.	6,7mm.	

ENVIRONMENTAL SPECIFICATIONS

Transportation & Storage Temperature	-40 / +70	°C
Installation Temperature	-20 / +60	°C
Operation Temperature	-25 / +60	°C
Relative Humidity	10 - 93, Non-condensing	%

PART NUMBER CODING

Part Nr. Product Description

T325A267 Zemecs 24 Port 1U UTP Patch Panel, Unloaded, Cable-Tie Free

APPLICATIONS

- 10G Base-T 10 Gigabit Ethernet*
- 1000 Base-T Gigabit Ethernet
- 100 Base-TX Fast Ethernet
- 10 Base-T Ethernet
- 622 Mbps ATM
- 155 Mbps ATM
- ISDN
- 4/16 Mbps Token Ring
- 100 Mbps TP-PMD
- Broadband and baseband video

COMPLIANCE

Standards For The Restriction Of Use Of Hazardous Substances In Electrical And **Electronic Equipments**

• 2011/65/EU (RoHS-2)







^{*} When used with jacks supporting 10G network speed