




OVERVIEW

Zemecs F111-L0 series fiber optic cables are designed and to exceed performances specified by ITU-T G652.D, IEC 60793, IEC 60974, ISO/IEC 11801 and TIA 568.3-D enabling high speed transmission to long distances in indoor and outdoor applications.

The fibers are constructed into a jelly filled loose tube wrapped by strengthening glass yarn on a water blocking layer. The PE sheathed cable is constructed up to 24 fibers and delivered in wooden drums of 500, 1.000 or 2.000m. They can be laid down on trays, ducts or pipes.



Drawing is not scaled.

FEATURES

- Exceeds requirements of ITU-T G652.D, IEC 60793, IEC 60974, ISO/IEC 11801 and TIA 568.3-D standards
- PE sheath
- Rodent protection through the use of glass yarn
- Gel filled cable core for water tightness
- Small outer diameter saving space inside ducts
- Low friction sheath enabling easy pulling through ducts
- Constructed up to 24 fibers

APPLICATIONS

- Indoor and outdoor network backbones
- Duct, pipe or tray installations
- Interbuilding cable crossings

MATERIAL AND PHYSICAL SPECIFICATIONS

Cable Outer Diameter	4-12F: 6,80	16-24F: 7,60	(± 0,20)	mm.
Sheath Material	LSOH (Low Smoke Zero Halogen)			
Sheath Thickness	4-12F: 1,80	16-24F: 2,20	(± 0,20)	mm.
Loose Tube Outer Diameter	3,00 ± 0,07			mm.
Cable Weight	4-12F: 55,00	16-24F: 68,00	(± %3)	kg./km.
Sheath Colour	Black(standard)			

COLOUR CODING OF FIBERS AND LOOSE TUBE

Fiber #	1	2	3	4	5	6	7	8	9	10	11	12
Colour	Blue	Orange	Green	Red	Grey	Yellow	Brown	Violet	Black	White	Pink	Aqua
Fiber #	13	14	15	16	17	18	19	20	21	22	23	24
Colour	Blue-Black	Orange-Black	Green-Black	Red-Black	Grey-Black	Yellow-Black	Brown-Black	Violet-Black	Black-Black	White-Black	Pink-Black	Aqua-Black



COMPLIANCE

Standards For Generic Cabling And Cabling Components

- ITU-T G652.D
- ISO/IEC 11801 V.2.1
- IEC 60793-2-50
- EN 50173
- IEC 60794-2-20
- ANSI/TIA/EIA-568.3-D

Standards For The Restriction Of Use Of Hazardous Substances In Electrical And Electronic Equipments

- 2011/65/EU (RoHS-2)

Test Standards

- | | | | |
|--------------------|-----------------|-----------------|-----------------|
| • Tension | IEC 60794-1-2E1 | • Twist | IEC 60794-1-2E7 |
| • Crush | IEC 60794-1-2E3 | • Cable Bending | IEC 60794-1-E11 |
| • Impact | IEC 60794-1-2E4 | • Temp.Cycling | IEC 60794-1-F1 |
| • Repeated Bending | IEC 60794-1-2E6 | | |

OPTICAL SPECIFICATIONS

Fiber Type	Singlemode ITU-T G652.D	
Attenuation (@1.310 nm./1.550nm.)	0,34 / 0,20	dB/km., Max.
Chromatic Dispersion (@1.310 nm./1.550nm.)	3,5 / 18	ps/(nm.km.), Max.
Zero Dispersion Wavelength (λ ₀)	1.300 ≤ λ ₀ ≤ 1.324	Nm.
Zero Dispersion Slope (S ₀)	0,092	ps/(nm ² .km.) Max.
Cable Cutoff Wavelength (λ _{cc})	1.260	nm., Max.

ENVIRONMENTAL SPECIFICATIONS

Transportation and Storage Temperature	-40 / + 80	°C
Installation Temperature	-30 / + 60	°C
Operation Temperature	-40 / + 80	°C
Relative Humidity	10 - 90, non-condensing	%

MECHANICAL SPECIFICATIONS

Tensile Strength (Installation/Operation)	1.500 / 600	N./100mm.
Crush Strength (Installation/Operation)	2.000 / 600	N./100mm.
Bending Radius (Installation/Operation)	20xO.D. / 10xO.D.	

GEOMETRICAL SPECIFICATIONS

Mode Field Diameter (@1.310nm./1.550nm.)	9,20 / 10,40	µm.
Cladding Diameter	125,0±1,0	µm.
Core/Coating Concentricity Error	1	%, Max.
Coating Diameter	245±7	µm.
Coating/Cladding Concentricity Error	12	µm., Max.
Core/Cladding Concentricity Error	0,6	µm., Max.

PART NUMBER CODING

Part Number	Product Description
F111-L0-1ESD-FFFY	Zemecs Singlemode Central Loose Tube Single Sheath Unarmoured PE Fiber Optic Cable

FFF: Fiber Count	Y: Length And Package Type
001 1	S 500m. Reel
002 2	M 1.000m. Reel
004 4	L 2.000m. Reel
006 6	
008 8	
012 12	
016 16	
024 24	

