



OVERVIEW

Zemecs Multimode OM3 SC couplers comply with ITU-T G.651, ANSI/TIA 568-3.D, EIA/TIA 492-AAAC-B, IEC 60874, IEC 61754 and ISO/IEC 11801 standards. They are used to connect pigtails to patch cords in indoor and outdoor panels and closures.

MATERIAL SPECIFICATIONS

COMPONENT	TYPE	MATERIAL	COLOUR
Housing	SC	Termoplastics	Aqua
Ferrule	N/A	Zirconia Ceramic	N/A
Flange	N/A	Stainless Steel	

OPTICAL SPECIFICATIONS

Insertion Loss @850nm.	0,30	dB., Max.
Return Loss	35	dB., Min.
Attenuation @850nm.	3,50	dB., Max.

ENVIRONMENTAL SPECIFICATIONS

Transportation and Storage Temperature	-40 / +85	°C
Installation Temperature	-40 / +85	°C
Operation Temperature	-40 / +85	°C
Relative Humidity	10 - 90, Non-condensing	%

FEATURES

- Return loss ≥ 35 dB
- -40°C / +85 °C operation temperature
- RoHS 2011/65/EU compliant
- With dust covers



APPLICATIONS

- Pigtail-patch cord connectivity in 40G and 10G fiber optic networks
- Fiber optic wall outlets
- Patch cords and panels

COMPLIANCE

Generic Cabling And Cabling Components Standards			
• ITU-T G.651.1	• IEC 60874-1		
• ANSI/TIA 568-3.D	• IEC 61754-4		
• ISO/IEC 11801	• IEC 60794		
Standards For The Restriction Of Use Of Hazardous Substances In Electrical And Electronic Equipments			
• 2011/65/EU (RoHS-2)			

PART NUMBER CODING

Part Nr.	Product Description
F5M3-41U2	Zemecs OM3 Duplex Coupler, SC
F5M3-41U1	Zemecs OM3 Simplex Coupler, SC