



RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors

(Front Door: Single Perforated, Rear Door: Single Perforated)



OVERVIEW


Zemecs RKUUS-DC2 series 19" standing type rack cabinets are designed and manufactured to accommodate IT hardware and equipments used by corporations of any scale. The front and rear doors are single perforated and products comply with IEC 60297-2 standard. They are offered from 9U to 52U heights and in sizes from 60x60cm. to 100x120cm. The broad accessory options enable effective utilization and facilitated maintenance of IT systems.

APPLICATIONS

- 19" device installation in data centers and server rooms

FEATURES

- Accommodation of 19" standard hardware
- Steel construction enabling heavy loading
- Available in heights from 20U to 52U; ability to supply at different heights
- 60x60, 60x80, 80x80, 60x100, 80x100, 100x100 and 100x120cm. size options
- Front door made of min. 70% perforated steel (circular or beehives design)
- Single perforated rear door (double door is optional)
- Easy to install and remove side panels with latch
- Clear marking of U height on front and rear vertical rails made of galvanized sheet metal
- Cooling units with 2, 4 or 6 fans and temperature control unit
- Simultaneous fitting of jacking feet and casters
- Front and rear doors with metal lock
- Optional dust proof brush type cable entry on front and bottom chassis
- Electrostatic powder coating on all surfaces
- Standard black (RAL9005) chassis; ability to supply at different colours
- May be delivered in multi departments on demand
- Wide choice of accessories
- Assembled or knock-down packing



RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors (Front Door: Single Perforated, Rear Door: Single Perforated)

GENERAL SPECIFICATIONS

Construction Material	DIN EN 10130 – 99 Compliant Cold Rolled Steel
Mounting Rails Material	Galvanized steel
Coating	Electrostatic powder coating on all surfaces
Colour	RAL 9005 or RAL 7035
Front Door	Single perforated steel door (optional double door)
Front Door Opening Angle	180°
Rear Door Type	Single perforated steel door (optional double door)
Lock	Handle type metal lock in plastic housing
Side Panels	Removable (latches)
Max. # Of Fans	6 (with temperature control unit)
Sheet Metal Thicknesses (mm.)	Frame & Rails: 1,50 Side Panels & Shelves: 1,20
Max. Load Capacity	800 kg.

ENVIRONMENTAL SPECIFICATIONS

Transportation & Storage Temperature	-40 / +85	°C
Installation Temperature	-20 / +85	°C
Operation Temperature	-20 / +85	°C
Relative Humidity	-10 / 90, Non-condensing	%


COMPLIANCE

Standards For Mechanical Structures For Electronic Equipment

• ANSI/EIA-310-E	• EN 60950-1
• DIN 41494 (Sections 1 & 7)	• IEC 60917
• EN 61587-1:2016	• EN 55022
• IEC 60297-2	• TS 822

Standards For The Restriction Of Use Of Hazardous Substances In Electrical And Electronic Equipments

• 2011/65/EU (RoHS-2)





RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors

(Front Door: Single Perforated, Rear Door: Single Perforated)

PHYSICAL SPECIFICATIONS-60x60cm. Racks

Part Nr.	Mounting Rail Height (U)	Inner Height (mm.)	Overall Height (mm.)	Width (mm.)	Depth (mm.)	Packaged Size (mm.)	Net Weight (kg.)	Gross Weight (kg.)
RK20S-402	20	888	1082	600	600	620x620x1082	47,34	49,83
RK25S-402	25	1110	1304	600	600	620x620x1304	52,41	55,17
RK27S-402	27	1199	1393	600	600	620x620x1393	54,53	57,40
RK30S-402	30	1333	1526	600	600	620x620x1526	58,42	61,50
RK33S-402	33	1466	1659	600	600	620x620x1659	61,37	64,60
RK35S-402	35	1555	1748	600	600	620x620x1748	63,97	67,33
RK37S-402	37	1644	1837	600	600	620x620x1837	66,09	69,57
RK39S-402	39	1733	1926	600	600	620x620x1926	68,68	72,30
RK42S-402	42	1866	2059	600	600	620x620x2059	69,25	72,90
RK45S-402	45	1999	2193	600	600	620x620x2193	81,22	85,50

PART NUMBER CODING

Part Nr.	Product Description
RKUUS-4C2	Zemecs 19" Standing Type 60x60cm. Rack With Perforated Doors

UU: Height	
20	20U
45	45U

C: Colour	
0	Black (RAL9005)
1	Light Grey (RAL7032)





RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors

(Front Door: Single Perforated, Rear Door: Single Perforated)

PHYSICAL SPECIFICATIONS-60x80cm. Racks

Part Nr.	Mounting Rail Height (U)	Inner Height (mm.)	Overall Height (mm.)	Width (mm.)	Depth (mm.)	Packaged Size (mm.)	Net Weight (kg.)	Gross Weight (kg.)
RK20S-502	20	888	1082	600	800	620x820x1082	54,10	56,94
RK25S-502	25	1110	1304	600	800	620x820x1304	60,38	63,56
RK27S-502	27	1199	1393	600	800	620x820x1393	62,89	66,20
RK30S-502	30	1333	1526	600	800	620x820x1526	66,66	70,17
RK33S-502	33	1466	1659	600	800	620x820x1659	70,43	74,13
RK35S-502	35	1555	1748	600	800	620x820x1748	73,41	77,28
RK37S-502	37	1644	1837	600	800	620x820x1837	75,45	79,42
RK39S-502	39	1733	1926	600	800	620x820x1926	77,96	82,07
RK42S-502	42	1866	2059	600	800	620x820x2059	82,21	86,53
RK45S-502	45	1999	2193	600	800	620x820x2193	85,50	90,00

PART NUMBER CODING

Part Nr.	Product Description
RKUUS-5C2	Zemecs 19" Standing Type 60x80cm. Rack With Perforated Doors

UU: Height	
20	20U
45	45U

C: Colour	
0	Black (RAL9005)
1	Light Grey (RAL7032)





RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors

(Front Door: Single Perforated, Rear Door: Single Perforated)

PHYSICAL SPECIFICATIONS-60x100cm. Racks

Part Nr.	Mounting Rail Height (U)	Inner Height (mm.)	Overall Height (mm.)	Width (mm.)	Depth (mm.)	Packaged Size (mm.)	Net Weight (kg.)	Gross Weight (kg.)
RK20S-602	20	888	1082	600	1000	620x1020x1082	61,33	64,56
RK25S-602	25	1110	1304	600	1000	620x1020x1304	68,35	71,94
RK27S-602	27	1199	1393	600	1000	620x1020x1393	71,25	75,00
RK30S-602	30	1333	1526	600	1000	620x1020x1526	75,37	79,33
RK33S-602	33	1466,00	1659	600	1000	620x1020x1659	79,48	83,67
RK35S-602	35	1555	1748	600	1000	620x1020x1748	81,91	86,22
RK37S-602	37	1644	1837	600	1000	620x1020x1837	85,29	89,78
RK39S-602	39	1733	1926	600	1000	620x1020x1926	88,19	92,83
RK42S-602	42	1866	2059	600	1000	620x1020x2059	91,83	96,67
RK45S-602	45	1999	2193	600	1000	620x1020x2193	96,42	101,50

PART NUMBER CODING

Part Nr.	Product Description
RKUUS-6C2	Zemecs 19" Standing Type 60x100cm. Rack With Perforated Doors

UU: Height	
20	20U
45	45U

C: Colour	
0	Black (RAL9005)
1	Light Grey (RAL7032)





RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors

(Front Door: Single Perforated, Rear Door: Single Perforated)

PHYSICAL SPECIFICATIONS-80x80cm. Racks

Part Nr.	Mounting Rail Height (U)	Inner Height (mm.)	Overall Height (mm.)	Width (mm.)	Depth (mm.)	Packaged Size (mm.)	Net Weight (kg.)	Gross Weight (kg.)
RK25S-702	25	1110	1304	800	800	820x820x1304	67,50	71,06
RK27S-702	27	1199	1393	800	800	820x820x1393	70,49	74,20
RK30S-702	30	1333	1526	800	800	820x820x1526	74,26	78,17
RK33S-702	33	1466	1659	800	800	820x820x1659	78,03	82,13
RK35S-702	35	1555	1748	800	800	820x820x1748	81,01	85,28
RK37S-702	37	1644	1837	800	800	820x820x1837	84,00	88,42
RK39S-702	39	1733	1926	800	800	820x820x1926	86,51	91,07
RK42S-702	42	1866	2059	800	800	820x820x2059	90,76	95,53
RK45S-702	45	1999	2193	800	800	820x820x2193	94,52	99,50


PART NUMBER CODING

Part Nr.	Product Description
RKUUS-7C2	Zemecs 19" Standing Type 80x80cm. Rack With Perforated Doors

UU: Height
20 20U
45 45U

C: Colour
0 Black (RAL9005)
1 Light Grey (RAL7032)





RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors

(Front Door: Single Perforated, Rear Door: Single Perforated)

PHYSICAL SPECIFICATIONS-80x100cm. Racks

Part Nr.	Mounting Rail Height (U)	Inner Height (mm.)	Overall Height (mm.)	Width (mm.)	Depth (mm.)	Packaged Size (mm.)	Net Weight (kg.)	Gross Weight (kg.)
RK20S-802	20	888	1082	800	1000	820x1020x1082	68,93	72,56
RK25S-802	25	1110	1304	800	1000	820x1020x1304	75,47	79,44
RK27S-802	27	1199	1393	800	1000	820x1020x1393	79,32	83,50
RK30S-802	30	1333	1526	800	1000	820x1020x1526	83,92	88,33
RK33S-802	33	1466	1659	800	1000	820x1020x1659	88,03	92,67
RK35S-802	35	1555	1748	800	1000	820x1020x1748	90,94	95,72
RK37S-802	37	1644	1837	800	1000	820x1020x1837	94,31	99,28
RK39S-802	39	1733	1926	800	1000	820x1020x1926	96,27	101,33
RK42S-802	42	1866	2059	800	1000	820x1020x2059	101,33	106,67
RK45S-802	45	1999	2193	800	1000	820x1020x2193	105,45	111,00

PART NUMBER CODING

Part Nr.	Product Description
RKUUS-8C2	Zemecs 19" Standing Type 80x100cm. Rack With Perforated Doors

UU: Height	
20	20U
45	45U

C: Colour	
0	Black (RAL9005)
1	Light Grey (RAL7032)



Table displays data for racks up to 45U height. Product can be delivered up to 52U height. Overall height includes casters.



RKUUS-DC2 Standing Type 19" Rack Cabinets With Perforated Doors

(Front Door: Single Perforated, Rear Door: Single Perforated)

PHYSICAL SPECIFICATIONS-100x100cm. Racks

Part Nr.	Mounting Rail Height (U)	Inner Height (mm.)	Overall Height (mm.)	Width (mm.)	Depth (mm.)	Packaged Size (mm.)	Net Weight (kg.)	Gross Weight (kg.)
RK20S-902	20	888	1082	1000	1000	1020x1020x1082	81,34	85,62
RK25S-902	25	1110	1304	1000	1000	1020x1020x1304	89,10	93,79
RK27S-902	27	1199	1393	1000	1000	1020x1020x1393	99,42	104,65
RK30S-902	30	1333	1526	1000	1000	1020x1020x1526	109,14	114,89
RK33S-902	33	1466	1659	1000	1000	1020x1020x1659	112,90	118,84
RK35S-902	35	1555	1748	1000	1000	1020x1020x1748	111,37	117,23
RK37S-902	37	1644	1837	1000	1000	1020x1020x1837	115,79	121,88
RK39S-902	39	1733	1926	1000	1000	1020x1020x1926	108,53	114,24
RK42S-902	42	1866	2059	1000	1000	1020x1020x2059	118,09	124,31
RK45S-902	45	1999	2193	1000	1000	1020x1020x2193	121,87	128,29

PART NUMBER CODING

Part Nr.	Product Description
RKUUS-9C2	Zemecs 19" Standing Type 100x100cm. Rack With Perforated Doors

UU: Height
20 20U
45 45U

C: Colour
0 Black (RAL9005)
1 Light Grey (RAL7032)

