



## OVERVIEW

Zemecs T115Z sries Category 5e S/FTP LSOH Solid LAN cables are designed and manufactured to exceed performances specified by ANSI/TIA/EIA-568-2.D, EN 50173, ISO/IEC 11801, IEC 61156-5 and EN 50288-5-1 standards up to 100 Mhz. Four twisted pairs of 24 AWG solid copper conductors are foiled individually which are then braided by tinned copper or aluminum manganese. Products with LSOH jacket are delivered in packages of 305 m. box, 500 and 1.000 m. reels.

Zemecs Category 5e S/FTP LAN cables support network speeds up to 1 Gigabit/s and their CPR compliance is third party certificated.



## FEATURES


- Exceeds requirements of ANSI/TIA/EIA-568-2.D, EN 50173, ISO/IEC 11801, IEC 61156-5 and EN 50288-5-1 cabling standards for channels, links and components
- Error free performance up to 1 Gigabit Ethernet at 100 Mhz.
- Guaranteed stable performance at all frequencies thanks to aluminum foil reducing impact of EMI
- Offered with different jacket colour and packages
- Easy identification of remaining cable through descending cable length marking

## APPLICATIONS

- 1000 Base-T Gigabit Ethernet
- 100 Base-TX Fast Ethernet
- 10 Base-T Ethernet
- 622 Mbps ATM
- 155 Mbps ATM
- ISDN
- 4/16 Mbps Token Ring
- 100 Mbps TP-PMD
- Broadband and baseband video

## MATERIAL AND PHYSICAL SPECIFICATIONS

<b>Conductor</b>	Material	100% Bare Annealed Copper
	Size	4x2x24 AWG
	Colour	Blue x Blue/White Strip
		Orange x Orange/White Strip
		Green x Green/White Strip
		Brown x Brown/White Strip
	Insulation	Polyolefin
	Insulation Diameter	0,95 ± 0,05 mm.
Pair Insulation	Aluminum Polyester Tape	
Braid	Tinned Copper Or Aluminum Manganese, Min. 30%	
<b>Jacket</b>	Material	LSOH (Low Smoke Zero Halogen)
	Outer Diameter	5,50 mm.± 0,15 mm.
<b>Drain Wire</b>	Material	0,40mm. Tinned Annealed Copper





## COMPLIANCE

Generic Cabling And Cabling Components Standards - Category 5e Requirements
• ISO/IEC 11801:2011 (V.2.2)
• IEC 61156 - 5:2012 (V. 2.1)
• EN 50173-1:2011
• EN 50173-2:2007 (Including A1:2010 amendmend)
• EN 50288-5-1:2013
• ANSI/TIA-568-2.D:2018
Flammability, Halogen Acidity And Smoke Performance
• IEC 60332-1-1:2015 (V.1.1), IEC 60332-1-2:2015 (V.1.1)
• IEC 60754-1:2011 (V.3.0), IEC 60754-2:2011 (V.2.0)
• IEC 61034-1:2013 (V.3.1), IEC 61034-2:2013 (V.3.1)
• EN 50575: 2014 + A1: 2016, EN 50399:2011+A1:2016
Standards For The Restriction Of Use Of Hazardous Substances In Electrical And Electronic Equipments
• 2011/65/EU (RoHS-2)

## TRANSMISSION PERFORMANCE

FREQUENCY (Mhz.)	INSERTION LOSS (dB., max)	RETURN LOSS (dB., min.)	NEXT (dB., min.)	PSNEXT (dB., min.)	ACR-F (dB., min.)	PS ACR-F (dB., min.)
1	1,9	27,8	88,9	86,9	83,1	80,1
4	3,6	37,1	83,7	81,7	76,3	73,3
8	5,0	39,1	77,8	75,8	72,7	69,7
10	5,6	41,4	73,6	71,6	66,7	63,7
16	7,2	47,9	70,1	68,1	60,2	57,2
20	8,3	46,0	71,9	69,9	58,1	55,1
25	9,4	41,2	68,7	66,7	58,5	55,5
31,25	10,4	38,0	63,4	61,4	58,9	55,9
62,5	14,9	35,3	60,9	58,9	48,2	45,2
100	19,2	29,0	56,2	54,2	42,3	39,3

Typical performance data for 100m. cable tested according to IEC 61156-5 at 20°C. Actual performance may vary depending on installation and environmental conditions.

## ENVIRONMENTAL AND PHYSICAL SPECIFICATIONS

Transportation and Storage Temperature	-20 / +80	°C
Installation Temperature	-20 / +60	°C
Operation Temperature	-20 / +60	°C
Relative Humidity	10 - 90, Non-condensing	%

## MECHANICAL SPECIFICATIONS

Tensile Strength	45	N./mm. <sup>2</sup> , Max.
Cold Bend Test @20 ± 2°C x 4 hour	No cracks occur	
Jacket Tensile Strength @ 100°C x 168 hour		
Before/After Aging	1.300 / 1.105	Psi,Min.
Jacket Elongation @ 100°C x 168 hour		
Before/After Aging	100 / 50	%,Min.
Insulation Tensile Strength@ 100°C x 48 hour		
Before/After Aging	2.400 / 1.800	Psi,Min.
Insulation Elongation @ 100°C x 48 hour		
Before/After Aging	300 / 225	%,Min.
Bending Radius		
Installation/Operation	8 / 4 x O.D.	mm.

## PART NUMBER CODING

Part Nr.	Product Description					
T115ZMXY	Zemecs Category 5e S/FTP 4x2x24# LSOH Solid LAN Cable					
<b>M: Jacket Colour</b>						
1	Light Grey	4	Red	7	Yellow	
2	Black	5	Green	8	Orange	
3	White	6	Blue	9	Violet	
<b>X: Length</b>						
1	305m.	2	500m.	3	1.000m.	
<b>Y: Package Type</b>						
B	Box	R	Reel	C	Reel In Box	

